

# POZZETTI FRIGO/FREEZER

## DUAL CHEST COOLER/FREEZER



### FRC 250 PFF

Frigo/Congelatore statico a pozzo vetro piatto scorrevole.  
Static chest cooler/freezer with flat sliding glass lids.



### FRC 300 PFF

Frigo/Congelatore statico a pozzo vetro piatto scorrevole.  
Static chest cooler/freezer with flat sliding glass lids.




### FRC 395 PFF

Frigo/Congelatore statico a pozzo vetro piatto scorrevole.  
Static chest cooler/freezer with flat sliding glass lids.







Ruote  
Castors



Cestelli  
Baskets



Termometro analogico  
Analogue thermometer



Dimensioni mm / Dimensions mm	FRC 250 PFF	FRC 300 PFF	FRC 395 PFF
Dimensioni Esterne (LxPxH) / External Dimensions (WxDxH)	834 x 653 x 900	1034 x 653 x 900	1234 x 653 x 900
Dimensioni Imballo (LxPxH) / Packaging Dimensions (WxDxH)	880 x 720 x 980	1080 x 720 x 980	1280 x 720 x 980
A - Larghezza / Width	683	883	1083
B - Profondità / Depth	505	505	505
C - Altezza / Height	645	645	645
E - Altezza Minima / Min. Height	365	365	365
F - Larghezza Minima / Min. Width	378	578	778
Adesivo Laterale Sinistro / Side Left Sticker	660 x 722	660 x 722	660 x 722
Adesivo Frontale / Front Sticker	860 x 712	1060 x 712	1260 x 712

Caratteristiche Tecniche / Technical Features	FRC 250 PFF	FRC 300 PFF	FRC 395 PFF
Temperatura / Temperature Range	0 °C / +10 °C -18 °C / 0 °C	0 °C / +10 °C -18 °C / 0 °C	0 °C / +10 °C -18 °C / 0 °C
Classe Climatica / Climate Class	4	4	4
Volume Netto-Lordo / Net-Gross Volume	Lt. 180 / 256	Lt. 244 / 336	Lt. 309 / 396
Superficie Esterna Body	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment
Superficie Interna Inner Liner	Alluminio preverniciato Precoated aluminium	Alluminio preverniciato Precoated aluminium	Alluminio preverniciato Precoated aluminium
Cestelli Baskets	560 x 280 x 208 mm Standard 2pz / 2pcs Optional (max 3pz / max 3pcs)	560 x 280 x 208 mm Standard 2pz / 2pcs Optional (max 4pz / max 4pcs)	560 x 280 x 208 mm Standard 2pz / 2pcs Optional (max 5pz / max 5pcs)
Termometro / Thermometer	Analogico / Analogue	Analogico / Analogue	Analogico / Analogue
Regolatore temperatura Controller	Meccanico Mechanical	Meccanico Mechanical	Meccanico Mechanical
Rumorosità / Noise level	dB 57	dB 57	dB 57
Spessore isolamento / Insulation thickness	mm 70	mm 70	mm 70
Sbrinamento / Defrost	Manuale / Manual	Manuale / Manual	Manuale / Manual
Illuminazione / Lighting	Led 3,7 W	Led 4 W	Led 4,5 W
Chiave e serratura / Lock and key	Si / Yes	Si / Yes	Si / Yes
Ruote-Piedi / Castors-Feet	4 Ruote (2 con freni) 4 Castors (2 with brakes)	4 Ruote (2 con freni) 4 Castors (2 with brakes)	4 Ruote (2 con freni) 4 Castors (2 with brakes)
Peso Netto-Lordo / Net-Gross Weight	Kg 43 / 55	Kg 48 / 61	Kg 53 / 68
Voltaggio / Voltage	V 220-240	V 220-240	V 220-240
Frequenza / Frequency	Hz 50	Hz 50	Hz 50
Refrigerante / Refrigerant	R290	R290	R290
Assorbimento / Absorption	W 200	W 240	W 250
Consumo Energia / Energy Consumption	KwH/24H 2,099	KwH/24H 3,681	KwH/24H 3,152