BANCHI REFRIGERATI COMPATTI > ESL SERIES
Compact refrigerated counters

GARANZIA 2 ANNI
2 YEAR WARRANTY
Ricambi e Manodopera
Spare Parts and Labour

GREEN LINE
R290 / R600a
GWP 3

INOX

PIANO IN ACCIAIO INOX
STAINLESS STEEL COUNTERTOP

OPTIONAL
Set 2 cassetti
In sostituzione di
1 porta x ESL
Vedi pag. 114
Set of 2 drawers
In replacement of door x ESL
(Please see p. 114)

RUOTE E PIEDI DI SERIE
WHEELS AND FEET AS STANDARD

ESL3820-GR
Banco refrigerato compatto con 4 cassetti* GN1/1
Compact refrigerated counter with 4 drawers GN1/1*

ESL3801-GR
Banco refrigerato compatto a 2 porte
Compact refrigerated counter with 2 doors

ESL3851-GR
Banco refrigerato compatto a 3 porte
Compact refrigerated counter with 3 doors

Profondità cassetti 150mm / *Drawer depth 150 mm

MODELLO / MODEL	ESL3820-GR	ESL3801-GR	ESL3851-GR
CLASSE ENERGETICA *Energy class*	B	A	A
CLASSE CLIMATICA *Climate class*	4 (30°C 55%)	4 (30°C 55%)	4 (30°C 55%)
DIMENSIONI PRODOTTO (mm) L×P×A *Product dimensions (mm) L×W×H*	900×700×943	900×700×943	1365×700×943
DIMENSIONE IMBALLO (mm) L×P×A *Packaging dimensions (mm) L×W×H*	955×754×1043	955×754×1043	1420×754×1043
PESO NETTO (Kg) *Net weight (Kg)*	82	72	94
PESO LORDO (Kg) *Gross weight (Kg)*	102	92	124
CAPACITÀ LORDA (L) *Gross capacity (L)*	300	300	380
TEMPERATURA (°C) *Temperature (°C)*	+2°C / +8°C	+2°C / +8°C	+2°C / +8°C
GRIGLIE IN DOTAZIONE PER PORTA *Grids supplied per door*	-	1	1
DIMENSIONE GRIGLIE (mm) *Grid size (mm)*	-	335×590	335×590
CARICO MASSIMO PER GRIGLIA (Kg) *Maximum load per grid (Kg)*	20	20	20
TERMOSTATO *Thermostat*	Dixell / Carel	Dixell / Carel	Dixell / Carel
COMPRESSORE *Compressor*	Huayi	Huayi	Huayi
MODELLO COMPRESSORE *Compressor model*	HYE105MXU	HYE105MXU	HYE105MXU
GAS REFRIGERANTE *Refrigerant gas*	R600a Isobutane - GWP3	R600a Isobutane - GWP3	R600a Isobutane - GWP3
CONSUMO ANNUO (KWh/anno) *Annual consumption (KWh/Year)*	529	423	584
VOLTAGGIO (V / Hz / Ph) *Voltage (V/Hz/Ph)*	220-240/50/1	220-240/50/1	220-240/50/1
POTENZA (W) *Power (W)*	220	220	220
TIPO REFRIGERAZIONE *Cooling method*	Ventilazione assistita / Fan assisted	Ventilazione assistita / Fan assisted	Ventilazione assistita / Fan assisted
SPESSORE COIBENTAZIONE (mm) *Insulation thickness (mm)*	35	35	35
SBRINAMENTO *Defrosting*	Ad aria / Air Defrost	Ad aria / Air Defrost	Ad aria / Air Defrost
PREZZO / PRICE	**€ 2.442,00**	**€ 1.329,00**	**€ 1.719,00**

Tutti i prezzi sono da intendersi al netto di IVA. Le specifiche tecniche potrebbero subire modifiche senza preavviso. Le immagini hanno il solo scopo di presentare il prodotto. Prezzi validi fino a nuova comunicazione.
All prices are exclusive of VAT. Prices are valid until further notice. Technical specifications are subject to change without prior notice. Images are for presentation purposes only.