# PORTACONDIMENTI REFRIGERATI > ESL SERIES

*Glass chilled and lid counters top GN pan holder*

**GARANZIA 2 ANNI**
***2 YEAR WARRANTY***
Ricambi e Manodopera
*Spare Parts and Labour*

**GREEN LINE**
R290 / R600a
GWP 3

**PIEDINI**
***FEET***
In dotazione
*Supplied*

## PORTACONDIMENTI REFRIGERATO CON TECA IN VETRO
***GLASS CHILLED COUNTER TOP GN PAN HOLDER***

| | |
|---|---|
| **ESL3880-GR** | VRX 1200/330 - 5 × GN1/4 |
| **ESL3881-GR** | VRX 1200/380 - 4 × GN1/3 |
| **ESL3861-GR** | VRX 1400/330 - 6 × GN1/4 |
| **ESL3882-GR** | VRX 1400/380 - 6 × GN1/3 |
| **ESL3883-GR** | VRX 1500/330 - 7 × GN1/4 |
| **ESL3884-GR** | VRX 1500/380 - 6 × GN1/3 |
| **ESL3885-GR** | VRX 1600/330 - 7 × GN1/4 |
| **ESL3886-GR** | VRX 1600/380 - 7 × GN1/3 |
| **ESL3887-GR** | VRX 1800/330 - 8 × GN1/4 |
| **ESL3888-GR** | VRX 1800/380 - 8 × GN1/3 |
| **ESL3889-GR** | VRX 2000/330 - 10 × GN1/4 |
| **ESL3890-GR** | VRX 2000/380 - 9 × GN1/3 |

## PORTACONDIMENTI REFRIGERATO CON COPERCHIO
***LID COUNTER TOP GN PAN HOLDER***

| | |
|---|---|
| **ESL3881S-GR** | VRX 1200/380 - 4 × GN1/3 |
| **ESL3882S-GR** | VRX 1400/380 - 6 × GN1/3 |
| **ESL3886S-GR** | VRX 1600/380 - 7 × GN1/3 |
| **ESL3890S-GR** | VRX 2000/380 - 9 × GN1/3 |

| GN | Prof. massima *Maximum depth* |
|---|---|
| 1/3 | 150 mm |
| 1/4 | 150 mm |

**Bacinelle NON INCLUSE disponibili separatamente Vedi pag. 186**

***Containers NOT INCLUDED available separately (please see p. 186)***

# PORTACONDIMENTI REFRIGERATO CON TECA IN VETRO > ESL SERIES

*Glass chilled counter top GN pan holder*

| MODELLO / MODEL | ESL3883-GR | ESL3884-GR | ESL3885-GR | ESL3886-GR |
|---|---|---|---|---|
| CLASSE ENERGETICA<br>*Energy class* | - | - | - | - |
| CLASSE CLIMATICA<br>*Climate class* | 4 (30°C 55%) | 4 (30°C 55%) | 4 (30°C 55%) | 4 (30°C 55%) |
| DIMENSIONI PRODOTTO (mm) L×P×A<br>*Product dimensions (mm) L×W×H* | 1505×335×465 | 1505×395×465 | 1605×335×465 | 1605×395×465 |
| DIMENSIONE IMBALLO (mm) L×P×A<br>*Packaging dimensions (mm) L×W×H* | 1565×415×430 | 1565×475×430 | 1665×415×430 | 1665×475×430 |
| PESO NETTO (Kg)<br>*Net weight (Kg)* | 43 | 47 | 45 | 49 |
| PESO LORDO (Kg)<br>*Gross weight (Kg)* | 69 | 74 | 73 | 78 |
| CAPACITÀ LORDA (L)<br>*Gross capacity (L)* | 44 | 53 | 48 | 58 |
| CONFIGURAZIONE<br>*Layout* | 7×GN1/4 | 6×GN1/3 | 7×GN1/4 | 7×GN1/3 |
| TEMPERATURA (°C)<br>*Temperature (°C)* | +2°C / +8°C | +2°C / +8°C | +2°C / +8°C | +2°C / +8°C |
| TERMOSTATO<br>*Thermostat* | Dixell / Carel | Dixell / Carel | Dixell / Carel | Dixell / Carel |
| COMPRESSORE<br>*Compressor* | Huayi | Huayi | Huayi | Huayi |
| MODELLO COMPRESSORE<br>*Compressor model* | HYB81MHUa | HYB81MHUa | HYB81MHUa | HYB81MHUa |
| GAS REFRIGERANTE<br>*Refrigerant gas* | R600a Isobutane - GWP3 | R600a Isobutane - GWP3 | R600a Isobutane - GWP3 | R600a Isobutane - GWP3 |
| CONSUMO ANNUO (KWh/anno)<br>*Annual consumption (KWh/Year)* | 566 | 566 | 566 | 566 |
| VOLTAGGIO (V / Hz / Ph)<br>*Voltage (V/Hz/Ph)* | 220-240/50/1 | 220-240/50/1 | 220-240/50/1 | 220-240/50/1 |
| POTENZA (W)<br>*Power (W)* | 180 | 180 | 180 | 180 |
| TIPO REFRIGERAZIONE<br>*Cooling method* | Statico / Static | Statico / Static | Statico / Static | Statico / Static |
| SPESSORE COIBENTAZIONE (mm)<br>*Insulation thickness (mm)* | 40 | 40 | 40 | 40 |
| SBRINAMENTO<br>*Defrosting* | Ad aria / Air Defrost | Ad aria / Air Defrost | Ad aria / Air Defrost | Ad aria / Air Defrost |
| **PREZZO / PRICE** | **€ 940,00** | **€ 958,00** | **€ 977,00** | **€ 1.002,00** |

Tutti i prezzi sono da intendersi al netto di IVA. Le specifiche tecniche potrebbero subire modifiche senza preavviso. Le immagini hanno il solo scopo di presentare il prodotto. Prezzi validi fino a nuova comunicazione.
*All prices are exclusive of VAT. Prices are valid until further notice. Technical specifications are subject to change without prior notice. Images are for presentation purposes only.*