PORTACONDIMENTI REFRIGERATI > ESL SERIES

Glass chilled and lid counters top GN pan holder

GARANZIA 2 ANNI
2 YEAR WARRANTY
Ricambi e Manodopera
Spare Parts and Labour

GREEN LINE
R290 / R600a
GWP 3

PIEDINI
FEET
In dotazione
Supplied

PORTACONDIMENTI REFRIGERATO CON TECA IN VETRO
GLASS CHILLED COUNTER TOP GN PAN HOLDER

ESL3880-GR	VRX 1200/330 - 5 × GN1/4
ESL3881-GR	VRX 1200/380 - 4 × GN1/3
ESL3861-GR	VRX 1400/330 - 6 × GN1/4
ESL3882-GR	VRX 1400/380 - 6 × GN1/3
ESL3883-GR	VRX 1500/330 - 7 × GN1/4
ESL3884-GR	VRX 1500/380 - 6 × GN1/3
ESL3885-GR	VRX 1600/330 - 7 × GN1/4
ESL3886-GR	VRX 1600/380 - 7 × GN1/3
ESL3887-GR	VRX 1800/330 - 8 × GN1/4
ESL3888-GR	VRX 1800/380 - 8 × GN1/3
ESL3889-GR	VRX 2000/330 - 10 × GN1/4
ESL3890-GR	VRX 2000/380 - 9 × GN1/3

PORTACONDIMENTI REFRIGERATO CON COPERCHIO
LID COUNTER TOP GN PAN HOLDER

ESL3881S-GR	VRX 1200/380 - 4 × GN1/3
ESL3882S-GR	VRX 1400/380 - 6 × GN1/3
ESL3886S-GR	VRX 1600/380 - 7 × GN1/3
ESL3890S-GR	VRX 2000/380 - 9 × GN1/3

GN	Prof. massima *Maximum depth*
1/3	150 mm
1/4	150 mm

Bacinelle NON INCLUSE disponibili separatamente Vedi pag. 186

Containers NOT INCLUDED available separately (please see p. 186)







MODELLO / MODEL	ESL3886S-GR	ESL3890S-GR
CLASSE ENERGETICA *Energy class*	-	-
CLASSE CLIMATICA *Climate class*	4 (30°C 55%)	4 (30°C 55%)
DIMENSIONI PRODOTTO (mm) L×P×A *Product dimensions (mm) L×W×H*	1605×395×300	2005×395×300
DIMENSIONE IMBALLO (mm) L×P×A *Packaging dimensions (mm) L×W×H*	1665×475×415	2065×475×415
PESO NETTO (Kg) *Net weight (Kg)*	31	56
PESO LORDO (Kg) *Gross weight (Kg)*	36	68
CAPACITÀ LORDA (L) *Gross capacity (L)*	58	76
CONFIGURAZIONE *Layout*	7×GN1/3	9×GN1/3
TEMPERATURA (°C) *Temperature (°C)*	+2°C / +8°C	+2°C / +8°C
TERMOSTATO *Thermostat*	Dixell / Carel	Dixell / Carel
COMPRESSORE *Compressor*	Huayi	Huayi
MODELLO COMPRESSORE *Compressor model*	HYB81MHUa	HYB81MHUa
GAS REFRIGERANTE *Refrigerant gas*	R600a Isobutane - GWP3	R600a Isobutane - GWP3
CONSUMO ANNUO (KWh/anno) *Annual consumption (KWh/Year)*	566	566
VOLTAGGIO (V / Hz / Ph) *Voltage (V/Hz/Ph)*	220-240/50/1	220-240/50/1
POTENZA (W) *Power (W)*	180	180
TIPO REFRIGERAZIONE *Cooling method*	Statico / Static	Statico / Static
SPESSORE COIBENTAZIONE (mm) *Insulation thickness (mm)*	40	40
SBRINAMENTO *Defrosting*	Ad aria / Air Defrost	Ad aria / Air Defrost
PREZZO / PRICE	**€ 1.167,00**	**€ 1.383,00**

Tutti i prezzi sono da intendersi al netto di IVA. Le specifiche tecniche potrebbero subire modifiche senza preavviso. Le immagini hanno il solo scopo di presentare il prodotto. Prezzi validi fino a nuova comunicazione.
All prices are exclusive of VAT. Prices are valid until further notice. Technical specifications are subject to change without prior notice. Images are for presentation purposes only.