



			BASIC 4	BASIC 44	BASIC 44 MEDIUM
MECHANICAL MECCANICO	Ø32				
CHAMBERS CAMERE		n°	1	2	2
PIZZE PIZZE n°		n°			
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	50 - 450	50 - 450	50 - 450
POWER I POTENZA		kW	4,7	9,4	9,4
TOP		W	2350x1	2350x2	2350x2
BOTTOM		W	2350x1	2350x2	2350x2
POWER SUPPLY ALIMENTAZIONE		volt	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	20,4	40,9	40,9
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Amp x phase	10,2	20,4	20,4
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**66,0** **66,0** **14,0**	**66,0** **66,0** **14,0**	**66,0** **66,0** **14,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	97,5 92,5 41,5	97,5 92,5 74,5	90,0 87,0 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	102,0 102,0 57,0	102,0 102,0 90,0	102,0 102,0 90,0
NET WEIGHT I PESO NETTO		kg	75,0	122,0	117,0
GROSS WEIGHT I PESO LORDO		kg	88,0	136,0	131,0
DIGITAL VERSION VERSIONE DIGITALE			o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA			o	o	o
INTERNAL LIGHT LUCE INTERNA			•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•

• **As standard** I Di serie o **Optional** I Optional