









MECHANICAL MECCANICO		BASIC 4	BASIC 44	BASIC 44 MEDIUM
CHAMBERS CAMERE	n°	1	2	2
PIZZE PIZZE n°	n°			
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	50 - 450	50 - 450	50 - 450
POWER I POTENZA	kW	4,7	9,4	9,4
TOP	W	2350x1	2350x2	2350x2
BOTTOM	W	2350x1	2350x2	2350x2
POWER SUPPLY ALIMENTAZIONE	volt	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase	20,4	40,9	40,9
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase	10,2	20,4	20,4
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H cm	**66,0** **66,0** **14,0**	**66,0** **66,0** **14,0**	**66,0** **66,0** **14,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H cm	97,5 92,5 41,5	97,5 92,5 74,5	90,0 87,0 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H cm	102,0 102,0 57,0	102,0 102,0 90,0	102,0 102,0 90,0
NET WEIGHT I PESO NETTO	kg	75,0	122,0	117,0
GROSS WEIGHT I PESO LORDO	kg	88,0	136,0	131,0
DIGITAL VERSION VERSIONE DIGITALE		o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA		o	o	o
INTERNAL LIGHT LUCE INTERNA		•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		•	•	•

• **As standard** I Di serie o **Optional** I Optional