



MECHANICAL MECCANICO		BASIC 6	BASIC 66	BASIC 6L	BASIC 66L
CHAMBERS CAMERE	n°	1	2	1	2
PIZZE PIZZE n°	n°				
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA	kW	7,2	14,4	7,2	14,4
TOP	W	1200x3	1200x6	1200x3	1200x6
BOTTOM	W	1200x3	1200x6	1200x3	1200x6
POWER SUPPLY ALIMENTAZIONE	volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase	31,3	62,6	31,3	62,6
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase	10,4	20,9	10,4	20,9
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H cm	**66,0** **99,0** **14,0**	**66,0** **99,0** **14,0**	**99,0** **66,0** **14,0**	**99,0** **66,0** **14,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H cm	97,5 121,5 41,5	97,5 121,5 74,5	130,5 93,0 41,5	130,5 93,0 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H cm	102,0 127,0 57,0	102,0 127,0 90,0	144,0 106,0 57,0	144,0 106,0 90,0
NET WEIGHT I PESO NETTO	kg	100,0	181,0	115,0	196,0
GROSS WEIGHT I PESO LORDO	kg	115,0	197,0	130,0	212,0
DIGITAL VERSION VERSIONE DIGITALE		o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA		o	o	o	o
INTERNAL LIGHT LUCE INTERNA		•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		•	•	•	•

• **As standard** I Di serie o **Optional** I Optional