



MECHANICAL MECCANICO		BASIC 6	BASIC 66	BASIC 6L	BASIC 66L
CHAMBERS CAMERE	n°	1	2	1	2
PIZZE PIZZE n°	n°				
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA	kW	7,2	14,4	7,2	14,4
TOP	W	1200x3	1200x6	1200x3	1200x6
BOTTOM	W	1200x3	1200x6	1200x3	1200x6
POWER SUPPLY ALIMENTAZIONE	volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase	31,3	62,6	31,3	62,6
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase	10,4	20,9	10,4	20,9
INTERNAL DIMENSIONS DIMENSIONI INTERNE	cm	**66,0** **99,0** **14,0**	**66,0** **99,0** **14,0**	**99,0** **66,0** **14,0**	**99,0** **66,0** **14,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	cm	97,5 121,5 41,5	97,5 121,5 74,5	130,5 93,0 41,5	130,5 93,0 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	cm	102,0 127,0 57,0	102,0 127,0 90,0	144,0 106,0 57,0	144,0 106,0 90,0
NET WEIGHT I PESO NETTO	kg	100,0	181,0	115,0	196,0
GROSS WEIGHT I PESO LORDO	kg	115,0	197,0	130,0	212,0
DIGITAL VERSION VERSIONE DIGITALE		o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA		o	o	o	o
INTERNAL LIGHT LUCE INTERNA		•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		•	•	•	•

• **As standard** I Di serie o **Optional** I Optional