



			BASIC XL 4	BASIC XL 44	BASIC XL 6	BASIC XL 66
MECHANICAL MECCANICO						
CHAMBERS CAMERE	n°		1	2	1	2
PIZZE PIZZE	n°					
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C		50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA	kW		6,0	12,0	9,0	18,0
TOP	W		3000x1	3000x2	1500x3	1500x6
BOTTOM	W		3000x1	3000x2	1500x3	1500x6
POWER SUPPLY ALIMENTAZIONE	volt		230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase		26,1	52,2	39,1	78,3
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase		13,0	26,1	13,0	26,1
INTERNAL DIMENSIONS DIMENSIONI INTERNE	cm	W D H	**72,0** **72,0** **14,0**	**72,0** **72,0** **14,0**	**72,0** **108,0** **14,0**	**72,0** **108,0** **14,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	cm	W D H	100,0 95,5 41,5	100,0 95,5 74,5	100,0 131,5 41,5	100,0 131,5 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	cm	W D H	102,0 102,0 57,0	102,0 102,0 90,0	106,0 144,0 57,0	106,0 144,0 90,0
NET WEIGHT I PESO NETTO	kg		77,0	139,0	110,0	198,0
GROSS WEIGHT I PESO LORDO	kg		90,0	153,0	125,0	215,0
DIGITAL VERSION VERSIONE DIGITALE			o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA			o	o	o	o
INTERNAL LIGHT LUCE INTERNA			•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE			o	o	o	o

• **As standard** I Di serie o **Optional** I Optional