

MECHANICAL MECCANICO		BASIC XL 6L	BASIC XL 66L	BASIC XL 9	BASIC XL 99
CHAMBERS CAMERE	n°	1	2	1	2
PIZZE PIZZE n°	n°				
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA	kW	9,0	18,0	13,2	26,4
TOP	W	1500x3	1500x6	2200x3	2200x6
BOTTOM	W	1500x3	1500x6	2200x3	2200x6
POWER SUPPLY ALIMENTAZIONE	volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase	39,1	78,3	57,4	114,8
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase	13,0	26,1	19,1	38,3
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H cm	**108,0** **72,0** **14,0**	**108,0** **72,0** **14,0**	**108,0** **108,0** **14,0**	**108,0** **108,0** **14,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H cm	136,0 95,5 41,5	136,0 95,5 74,5	136,0 131,5 41,5	136,0 131,5 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H cm	144,0 106,0 57,0	144,0 106,0 90,0	144,0 142,0 57,0	144,0 142,0 90,0
NET WEIGHT I PESO NETTO	kg	118,0	176,0	156,0	269,0
GROSS WEIGHT I PESO LORDO	kg	136,0	197,0	176,0	300,0
DIGITAL VERSION VERSIONE DIGITALE		o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA		o	o	o	o
INTERNAL LIGHT LUCE INTERNA		•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE		o	o	o	o

• **As standard** I Di serie o **Optional** I Optional