


Specify methane gas or LPG (butane or propane)
Specificare tipo di gas: metano o GPL (butano o propano)
An der Bestellung muß man entweder Methan oder Flüssiggas (Butan oder Propan) genau angeben
Spécifier le type de gaz: méthane ou Gaz de Pétrole Liquéfié (butane or propane)
Especifique el tipo de gas: metano o GLP (butano o propano)
При заказе указать тип газа: метан или сжиженный нефтяной газ (бутан или пропан



MECHANICAL MECCANICO		GAS 4	GAS 6	GAS 9
CHAMBERS CAMERE	n°	1	1	1
PIZZE PIZZE	n°			
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	0 - 450	0 - 450	0 - 450
POWER I POTENZA	kW	16,1	21,5	27,0
	BTU/hr	55000	73000	92000
	kcal/h	13800	18500	23200
POWER SUPPLY ALIMENTAZIONE	volt	230	230	230
GAS CONSUMPTION CONSUMO GAS	kg/h	1,262 (G 30/31)	1,696 (G 30/31)	2,129 (G 30/31)
	m^3/h	1,693 (G 20)	2,275 (G 20)	2,852 (G 20)
	m^3/h	1,693 (G 25)	2,275 (G 25)	2,852 (G 25)
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W cm	**61,0**	**61,0**	**91,0**
	D	**60,0**	**90,0**	**90,0**
	H	**15,0**	**15,0**	**15,0**
EXTERNAL DIMENSIONS (with chimney) DIMENSIONI ESTERNE (con camino)	W cm	100,0	100,0	130,0
	D	106,0	136,0	136,0
	H	54,0	54,0	54,0
PACKING DIMENSIONS DIMENSIONI IMBALLO	W cm	104,0	104,0	138,0
	D	94,0	125,0	125,0
	H	60,0	60,0	60,0
NET WEIGHT I PESO NETTO	kg	96,0	123,0	156,0
GROSS WEIGHT I PESO LORDO	kg	108,0	138,0	175,0
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA		o	o	o
INTERNAL LIGHT LUCE INTERNA		•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		•	•	•
WINDPROOF CHIMNEY CAMINO ANTIVENTO		o	o	o
CHIMNEY CONNECTION FOR STACKABLE OVENS RACCORDO PER FORNI A GAS DA SOVRAPPORRE		o	o	o

• **As standard** I Di serie o **Optional** I Optional