





			GAS XL 4	GAS XL 6
MECHANICAL MECCANICO	Ø35			
CHAMBERS CAMERE		n°	1	1
PIZZE PIZZE n°		n°		
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	0 - 450	0 - 450
POWER I POTENZA		kW	18,0	23,0
		BTU/hr	61000	78000
		kcal/h	15500	19800
POWER SUPPLY ALIMENTAZIONE		volt	230	230
GAS CONSUMPTION CONSUMO GAS		kg/h	1,432 (G 30/31)	1,933 (G 30/31)
		m^3/h	1,954 (G 20)	2,725 (G 20)
		m^3/h	2,491 (G 25)	3,149 (G 25)
INTERNAL DIMENSIONS DIMENSIONI INTERNE		W D H cm	**72,0** **72,0** **15,0**	**72,0** **108,0** **15,0**
EXTERNAL DIMENSIONS (with chimney) DIMENSIONI ESTERNE (con camino)		W D H cm	111,0 118,0 54,0	111,0 154,0 54,0
PACKING DIMENSIONS DIMENSIONI IMBALLO		W D H cm	116,0 116,0 60,0	119,0 143,0 60,0
NET WEIGHT I PESO NETTO		kg	113,0	145,0
GROSS WEIGHT I PESO LORDO		kg	127,0	162,0
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA			o	o
INTERNAL LIGHT LUCE INTERNA			o	o
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•
WINDPROOF CHIMNEY CAMINO ANTIVENTO			o	o
CHIMNEY CONNECTION FOR STACKABLE OVENS RACCORDO PER FORNI A GAS DA SOVRAPPORRE			o	o

• **As standard** I Di serie o **Optional** I Optional