



H9

Ø35

MECHANICAL MECCANICO		HIDEO 1/40	HIDEO 2/40
CHAMBERS CAMERE	n°	1	2
PIZZE PIZZE n°	n°	●	● + ●
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	50 - 320	50 - 320
POWER I POTENZA	kW	1,6	3,2
TOP	W	800x1	800x2
BOTTOM	W	800x1	800x2
POWER SUPPLY ALIMENTAZIONE	volt	230	230
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase	7,0	13,9
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase	–	–
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H cm	**41,0** **36,0** **9,0**	**41,0** **36,0** **9,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H cm	59,5 50,0 28,5	59,5 50,0 46,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H cm	67,0 60,0 34,0	67,0 60,0 51,0
NET WEIGHT I PESO NETTO	kg	30,0	38,0
GROSS WEIGHT I PESO LORDO	kg	32,0	44,0
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		●	●

● **As standard** I Di serie ○ **Optional** I Optional

Rock wool insulation

Isolamento in lana di roccia evaporata

Isolierung aus verdampfter Mineralwolle

Isolation en laine de roche évaporée

Aislamiento en lana de roca evaporada

Изоляция из каменной ваты