


STAINLESS STEEL CHAMBER

HEAT-IN STONE



MECHANICAL MECCANICO		MAIOR 6L	MAIOR 66L	MAIOR 9	MAIOR 99
CHAMBERS CAMERE	n°	1	2	1	2
PIZZE PIZZE n°	n°	Ø35	Ø35 + Ø35	Ø35	Ø35 + Ø35
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA	kW	9,9	19,8	14,4	28,8
TOP	W	550x9	550x18	800x9	800x18
BOTTOM	W	550x9	550x18	800x9	800x18
POWER SUPPLY ALIMENTAZIONE	volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase	43,0	86,0	62,5	125,0
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase	14,5	29,0	21,0	42,0
INTERNAL DIMENSIONS DIMENSIONI INTERNE	cm	**108,0** **72,0** **16,0**	**108,0** **72,0** **16,0**	**108,0** **108,0** **16,0**	**108,0** **108,0** **16,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	cm	146,0 100,0 40,0	146,0 100,0 72,0	146,0 136,0 40,0	146,0 136,0 72,0
PACKING DIMENSIONS DIMENSIONI IMBALLO	cm	154,0 114,0 54,0	154,0 114,0 86,0	158,0 142,0 54,0	158,0 142,0 86,0
NET WEIGHT I PESO NETTO	kg	143,0	258,0	183,0	330,0
GROSS WEIGHT I PESO LORDO	kg	160,0	280,0	212,0	363,0
DIGITAL VERSION VERSIONE DIGITALE		o	o	o	o
STAINLESS STEEL CHAMBER CAMERA IN ACCIAIO INOX		•	•	•	•
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA		•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE		o	o	o	o

• **As standard** I Di serie o **Optional** I Optional