PLUS XL OVENS

MECHANICAL MECCANICO		PLUS XL 4	PLUS XL 44	PLUS XL 6	PLUS XL 66
CHAMBERS CAMERE	n°	1	2	1	2
PIZZE PIZZE	n°	Ø35	Ø35 + Ø35	Ø35	Ø35 + Ø35
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA	kW	6,0	12,0	9,0	18,0
TOP	W	1000x3	1000x6	1500x3	1500x6
BOTTOM	W	1000x3	1000x6	1500x3	1500x6
POWER SUPPLY ALIMENTAZIONE	volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase	26,1	52,2	39,1	78,3
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase	8,7	17,4	13,0	26,1
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H cm	**72,0** **72,0** **14,0**	**72,0** **72,0** **14,0**	**72,0** **108,0** **14,0**	**72,0** **108,0** **14,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H cm	100,0 96,0 41,5	100,0 96,0 74,5	100,0 132,0 41,5	100,0 132,0 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H cm	102,0 102,0 57,0	102,0 102,0 90,0	106,0 144,0 57,0	106,0 144,0 90,0
NET WEIGHT I PESO NETTO	kg	85,0	162,0	115,0	203,0
GROSS WEIGHT I PESO LORDO	kg	98,0	176,0	130,0	220,0
DIGITAL VERSION VERSIONE DIGITALE		o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA		o	o	o	o
INTERNAL LIGHT LUCE INTERNA		•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE		o	o	o	o

• **As standard** I Di serie o **Optional** I Optional