


SUPERIOR XL GLASS OVENS














			SUPERIOR XL 4 GLASS	SUPERIOR XL 44 GLASS	SUPERIOR XL 6 GLASS	SUPERIOR XL 66 GLASS
MECHANICAL MECCANICO	Ø35					
CHAMBERS CAMERE		n°	1	2	1	2
PIZZE PIZZE n°		n°		+		+
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER | POTENZA		kW	6,0	12,0	9,0	18,0
TOP		W	1000x3	1000x6	1500x3	1500x6
BOTTOM		W	1000x3	1000x6	1500x3	1500x6
POWER SUPPLY ALIMENTAZIONE		volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	26,1	52,2	39,1	78,3
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Amp x phase	8,7	17,4	13,0	26,1
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**72,0** **72,0** **14,0**	**72,0** **72,0** **14,0**	**72,0** **108,0** **14,0**	**72,0** **108,0** **14,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	100,0 94,0 41,5	100,0 94,0 74,5	100,0 130,0 41,5	100,0 130,0 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	102,0 102,0 57,0	102,0 102,0 90,0	106,0 144,0 57,0	106,0 144,0 90,0
NET WEIGHT | PESO NETTO		kg	85,4	154,4	115,0	205,0
GROSS WEIGHT | PESO LORDO		kg	98,5	168,8	130,0	213,0
DIGITAL VERSION VERSIONE DIGITALE			o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA			o	o	o	o
INTERNAL LIGHT LUCE INTERNA			•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE			o	o	o	o

• **As standard** | Di serie o **Optional** | Optional