



MECHANICAL MECCANICO			SUPERIOR XL 6L GLASS	SUPERIOR XL 66L GLASS	SUPERIOR XL 9 GLASS	SUPERIOR XL 99 GLASS
CHAMBERS CAMERE		n°	1	2	1	2
PIZZE PIZZE n°		n°	Ø35	Ø35 + Ø35	Ø35	Ø35 + Ø35
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER | POTENZA		kW	9,0	18,0	13,2	26,4
TOP		W	1500x3	1500x6	2200x3	2200x6
BOTTOM		W	1500x3	1500x6	2200x3	2200x6
POWER SUPPLY ALIMENTAZIONE		volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	39,1	78,3	57,4	114,8
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Amp x phase	13,0	26,1	19,1	38,3
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**108,0** **72,0** **14,0**	**108,0** **72,0** **14,0**	**108,0** **108,0** **14,0**	**108,0** **108,0** **14,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	136,0 94,0 41,5	136,0 94,0 74,5	136,0 130,0 41,5	136,0 130,0 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	144,0 106,0 57,0	144,0 106,0 90,0	142,0 144,0 57,0	142,0 144,0 90,0
NET WEIGHT | PESO NETTO		kg	119,8	218,0	170,0	280,0
GROSS WEIGHT | PESO LORDO		kg	138,0	239,0	190,0	311,0
DIGITAL VERSION VERSIONE DIGITALE			o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA			o	o	o	o
INTERNAL LIGHT LUCE INTERNA			•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE			o	o	o	o

• **As standard** | Di serie o **Optional** | Optional