













		TRAYS 4 GLASS	TRAYS 44 GLASS	TRAYS 6 GLASS	TRAYS 66 GLASS
MECHANICAL MECCANICO			Ø40		Ø35
CHAMBERS CAMERE	n°	1	2	1	2
PIZZE PIZZE n°	n°				
TRAYS 40X60 TEGLIE 40X60	n°				
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA	kW	6,9	13,8	10,2	20,4
TOP	W	1150x3	1150x6	1700x3	1700x6
BOTTOM	W	1150x3	1150x6	1700x3	1700x6
POWER SUPPLY ALIMENTAZIONE	volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase	30,0	60,0	44,3	88,7
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase	10,0	20,0	14,8	29,6
INTERNAL DIMENSIONS DIMENSIONI INTERNE	cm	**82,0** **84,0** **17,5**	**82,0** **84,0** **17,5**	**82,0** **108,0** **17,5**	**82,0** **108,0** **17,5**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	cm	110,0 108,0 41,5	110,0 108,0 74,5	110,0 132,0 41,5	110,0 132,0 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	cm	115,0 115,0 57,0	115,0 115,0 90,0	118,0 142,0 57,0	118,0 142,0 90,0
NET WEIGHT I PESO NETTO	kg	98,0	172,0	123,0	220,0
GROSS WEIGHT I PESO LORDO	kg	114,0	189,0	145,0	236,0
DIGITAL VERSION VERSIONE DIGITALE		o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA		o	o	o	o
INTERNAL LIGHT LUCE INTERNA		•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE		o	o	o	o
STEAM GENERATOR VAPORIERA		o	–	o	–

• **As standard** I Di serie o **Optional** I Optional