







H17,5









			TRAYS 4	TRAYS 44	TRAYS 6	TRAYS 66
MECHANICAL MECCANICO				Ø40		Ø35
CHAMBERS CAMERE		n°	1	2	1	2
PIZZE PIZZE n°		n°				
TRAYS 40X60 TEGLIE 40X60		n°				
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA		kW	6,9	13,8	10,2	20,4
TOP		W	1150x3	1150x6	1700x3	1700x6
BOTTOM		W	1150x3	1150x6	1700x3	1700x6
POWER SUPPLY ALIMENTAZIONE		volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	30,0	60,0	44,3	88,7
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Amp x phase	10,0	20,0	14,8	29,6
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**82,0** **84,0** **17,5**	**82,0** **84,0** **17,5**	**82,0** **108,0** **17,5**	**82,0** **108,0** **17,5**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	110,0 108,0 41,5	110,0 108,0 74,5	110,0 132,0 41,5	110,0 132,0 74,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	116,0 116,0 57,0	116,0 116,0 90,0	119,0 143,0 57,0	119,0 143,0 90,0
NET WEIGHT I PESO NETTO		kg	98,0	154,0	123,0	220,0
GROSS WEIGHT I PESO LORDO		kg	114,0	171,0	145,0	236,0
DIGITAL VERSION VERSIONE DIGITALE			o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA			o	o	o	o
INTERNAL LIGHT LUCE INTERNA			•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE			o	o	o	o
STEAM GENERATOR VAPORIERA			o	–	o	–

• **As standard** I Di serie o **Optional** I Optional