			BASIC 1/40	BASIC 1/40 VETRO	BASIC 1/40 VETRO 2T	BASIC ALTO 1/40 VETRO 2T
MECHANICAL MECCANICO	Ø32					
CHAMBERS CAMERE		n°	1	1	1	1
PIZZE PIZZE n°		n°				
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	50 - 320	50 - 320	50 - 320	50 - 320
POWER I POTENZA		kW	1,6	1,6	1,6	1,6
TOP		W	800x1	800x1	800x1	800x1
BOTTOM		W	800x1	800x1	800x1	800x1
POWER SUPPLY ALIMENTAZIONE		volt	230	230	230	230
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	7,0	7,0	7,0	7,0
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Amp x phase	–	–	–	–
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**41,0** **36,0** **9,0**	**41,0** **36,0** **9,0**	**41,0** **36,0** **9,0**	**41,0** **36,0** **18,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	61,5 50,0 28,0	61,5 50,0 28,0	61,5 50,0 28,0	61,5 50,0 36,5
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	67,0 60,0 34,0	67,0 60,0 34,0	67,0 60,0 34,0	67,0 60,0 42,0
NET WEIGHT I PESO NETTO		kg	22,0	22,0	24,0	29,0
GROSS WEIGHT I PESO LORDO		kg	24,0	24,0	26,0	31,0
INTERNAL LIGHT LUCE INTERNA			–	o	o	•
TIMER TIMER			•	•	–	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•

• **As standard** I Di serie o **Optional** I Optional