STAINLESS STEEL CHAMBER



H16

Ø35

			DHOME 4	DHOME 44	DHOME 6	DHOME 66
DIGITAL DIGITALE						
CHAMBERS CAMERE		n°	1	2	1	2
PIZZE PIZZE		n°				
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	30 - 430	30 - 430	30 - 430	30 - 430
POWER I POTENZA		kW	6,8	13,6	9,8	19,6
TOP		W	1000x3+800x1	1000x6+800x2	1500x3+800x1	1500x6+800x2
BOTTOM		W	1000x3	1000x6	1500x3	1500x6
POWER SUPPLY ALIMENTAZIONE		volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	29,6	59,1	42,6	85,2
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Max Amp x phase	13,0	26,1	19,6	39,1
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**72,0** **72,0** **16,0**	**72,0** **72,0** **16,0**	**72,0** **108,0** **16,0**	**72,0** **108,0** **16,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	120,0 100,5 40,0	120,0 100,5 72,0	120,0 136,5 40,0	120,0 136,5 72,0
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	144,0 106,0 54,0	144,0 106,0 86,0	133,0 154,0 54,0	133,0 154,0 86,0
NET WEIGHT I PESO NETTO		kg	91,0	160,0	120,0	212,0
GROSS WEIGHT I PESO LORDO		kg	109,0	180,0	141,0	235,0
STAINLESS STEEL CHAMBER CAMERA IN ACCIAIO INOX			•	•	•	•
STAINLESS STEEL FRAME CORNICE IN ACCIAIO INOX			o	o	o	o
INTERNAL LED LIGHT ILLUMINAZIONE INTERNA A LED			•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•

• **As standard** I Di serie o **Optional** I Optional