

STAINLESS STEEL CHAMBER

H16

Ø35



			DHOME 6L	DHOME 66L	DHOME 9	DHOME 99
DIGITAL DIGITALE						
CHAMBERS CAMERE		n°	1	2	1	2
PIZZE PIZZE		n°				
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	30 - 430	30 - 430	30 - 430	30 - 430
POWER I POTENZA		kW	9,8	19,6	14,0	28,0
TOP		W	1500x3+800x1	1500x6+800x2	2200x3+800x1	2200x6+800x2
BOTTOM		W	1500x3	1500x6	2200x3	2200x6
POWER SUPPLY ALIMENTAZIONE		volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	42,6	85,2	60,9	121,7
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Max Amp x phase	19,6	39,1	28,7	57,4
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**108,0** **72,0** **16,0**	**108,0** **72,0** **16,0**	**108,0** **108,0** **16,0**	**108,0** **108,0** **16,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	156,0 100,5 40,0	156,0 100,5 72,0	156,0 136,5 40,0	156,0 136,5 72,0
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	162,0 107,0 54,0	162,0 107,0 86,0	162,0 142,0 54,0	162,0 142,086,0
NET WEIGHT I PESO NETTO		kg	124,0	221,0	165,0	294,0
GROSS WEIGHT I PESO LORDO		kg	144,0	242,0	190,0	320,0
STAINLESS STEEL CHAMBER CAMERA IN ACCIAIO INOX			•	•	•	•
STAINLESS STEEL FRAME CORNICE IN ACCIAIO INOX			o	o	o	o
INTERNAL LED LIGHT ILLUMINAZIONE INTERNA A LED			•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•

• **As standard** I Di serie o **Optional** I Optional