






MECHANICAL MECCANICO			MAIOR LE UP 4	MAIOR LE UP 44	MAIOR LE UP 6	MAIOR LE UP 66
CHAMBERS CAMERE		n°	1	2	1	2
PIZZE PIZZE		n°	Ø35	Ø35 + Ø35	Ø35	Ø35 + Ø35
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA		kW	6,0	12,0	9,0	18,0
TOP		W	1000x3	1000x6	1500x3	1500x6
BOTTOM		W	1000x3	1000x6	1500x3	1500x6
POWER SUPPLY ALIMENTAZIONE		volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	26,1	52,2	39,1	78,3
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Amp x phase	8,7	17,4	13,0	26,1
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**72,0** **72,0** **16,0**	**72,0** **72,0** **16,0**	**72,0** **108,0** **16,0**	**72,0** **108,0** **16,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	110,0 100,0 40,0	110,0 100,0 72,0	110,0 136,0 40,0	110,0 136,0 72,0
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	115,0 115,0 54,0	115,0 115,0 86,0	118,0 142,0 54,0	118,0 142,0 86,0
NET WEIGHT I PESO NETTO		kg	108,0	194,0	137,0	246,0
GROSS WEIGHT I PESO LORDO		kg	124,0	211,0	159,0	262,0
DIGITAL VERSION VERSIONE DIGITALE			o	o	o	o
STAINLESS STEEL CHAMBER CAMERA IN ACCIAIO INOX			o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA			•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE			o	o	o	o

• **As standard** I Di serie o **Optional** I Optional