

OPTIONAL

Stainless steel chamber	Chambre en inox
Camera in acciaio inox	Cámara de acero inoxidable
Edelstahlkammer	Камера из нержавейки



MECHANICAL MECCANICO			MAIOR LE UP 6L	MAIOR LE UP 66L	MAIOR LE UP 9	MAIOR LE UP 99
CHAMBERS CAMERE	Ø35	n°	1	2	1	2
PIZZE PIZZE		n°		+		+
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA		kW	9,0	18,0	13,2	26,4
TOP		W	1500x3	1500x6	2200x3	2200x6
BOTTOM		W	1500x3	1500x6	2200x3	2200x6
POWER SUPPLY ALIMENTAZIONE		volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	39,1	78,3	57,4	114,8
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Amp x phase	13,0	26,1	19,1	38,3
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**108,0** **72,0** **16,0**	**108,0** **72,0** **16,0**	**108,0** **108,0** **16,0**	**108,0** **108,0** **16,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	146,0 100,0 40,0	146,0 100,0 72,0	146,0 136,0 40,0	146,0 136,0 72,0
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	154,0 114,0 54,0	154,0 114,0 86,0	158,0 142,0 54,0	158,0 142,0 86,0
NET WEIGHT I PESO NETTO		kg	143,0	258,0	183,0	330,0
GROSS WEIGHT I PESO LORDO		kg	160,0	280,0	212,0	363,0
DIGITAL VERSION VERSIONE DIGITALE			o	o	o	o
STAINLESS STEEL CHAMBER CAMERA IN ACCIAIO INOX			o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA			•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE			o	o	o	o

• **As standard** I Di serie o **Optional** I Optional