

OPTIONAL

STAINLESS STEEL CHAMBER	**Stainless steel chamber**	Chambre en inox
	Camera in acciaio inox	Cámara de acero inoxidable
	Edelstahlkammer	Камера из нержавейки



MECHANICAL MECCANICO			MAIOR LE UP 6L	MAIOR LE UP 66L	MAIOR LE UP 9	MAIOR LE UP 99
CHAMBERS CAMERE		n°	1	2	1	2
PIZZE PIZZE	Ø35	n°				
WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO		°C	50 - 450	50 - 450	50 - 450	50 - 450
POWER I POTENZA		kW	9,0	18,0	13,2	26,4
TOP		W	1500x3	1500x6	2200x3	2200x6
BOTTOM		W	1500x3	1500x6	2200x3	2200x6
POWER SUPPLY ALIMENTAZIONE		volt	230 - 400	230 - 400	230 - 400	230 - 400
ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE		Amp x phase	39,1	78,3	57,4	114,8
ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE		Amp x phase	13,0	26,1	19,1	38,3
INTERNAL DIMENSIONS DIMENSIONI INTERNE	W D H	cm	**108,0** **72,0** **16,0**	**108,0** **72,0** **16,0**	**108,0** **108,0** **16,0**	**108,0** **108,0** **16,0**
EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	W D H	cm	146,0 100,0 40,0	146,0 100,0 72,0	146,0 136,0 40,0	146,0 136,0 72,0
PACKING DIMENSIONS DIMENSIONI IMBALLO	W D H	cm	154,0 114,0 54,0	154,0 114,0 86,0	158,0 142,0 54,0	158,0 142,0 86,0
NET WEIGHT I PESO NETTO		kg	143,0	258,0	183,0	330,0
GROSS WEIGHT I PESO LORDO		kg	160,0	280,0	212,0	363,0
DIGITAL VERSION VERSIONE DIGITALE			o	o	o	o
STAINLESS STEEL CHAMBER CAMERA IN ACCIAIO INOX			o	o	o	o
12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA			•	•	•	•
REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA			•	•	•	•
OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE			o	o	o	o

• **As standard** I Di serie o **Optional** I Optional